



Creating The Future  
Of Optical Transceiver

Rev.1C: 100G/200G/400G

## ABOUT US

Eoptolink Technology Inc., Ltd. is dedicated to research, develop, manufacture and market a diverse portfolio of high-performance, cost-competitive optical transceiver modules for: Datacenter, LTE/Wireless, Enterprise, Access, Metro, Core, Broadcast(SMPTE), SAN applications for the customers all round the world.

## HIGHLIGHTS:

- Founded in 2008, HQ: Chengdu, China
- Factory: 35000m2
- ISO9001:2008, ISO14001:2004, TUV, CE, UL, FCC, FDA, RoHS, REACH and EMC certified.
- Error free and reliable transceivers for any applications
- Short & long run manufacturing flexibility
- Prompt lead time & technical support
- More than 3000 transceiver types
- Customized transceivers service
- Advanced R&D resources
- Tier 1 equipment manufacturers qualified



## Contact

Tel: +86-28-6708 7983

Fax: +86-28-6708 7979

Web: [www.eoptolink.com](http://www.eoptolink.com)

Address: No.127 West Wulian Street,  
Chengdu 610213, China.

Sales Department: [sales@eoptolink.com](mailto:sales@eoptolink.com)

QSFP28	Part No.	Product Description	Data Rate	Wavelength	Temp.	Distance
	EOLQ-851HG-02-MO	QSFP28 SR4	4×25G 100GbE	850nm	0°C~70°C	100m
	EOLQ-131HG-5H-MO	QSFP28 PSM4	4×25G 100GbE	1310nm	0°C~70°C	500m
	EOLQ-1HG-PCT-XX	QSFP28 AOC	4×25G 100GbE	850nm	0°C~70°C	100m
	EOLQ-161HG-02-B	QSFP28 CWDM4/CLR4	4×25G 100GbE 4×28G OTU4	1271nm/1291nm 1311nm/1331nm	0°C~70°C	2km
	EOLQ-161HG-10-L(B)	QSFP28 LR4	4×25G 100GbE (4×28G OTU4)	1295nm/1300nm 1305nm/1310nm	0°C~70°C	10km
EOLQ-161HG-10LA	QSFP28 LR4	4×25G 100GbE 4×28G OTU4	1295nm/1300nm 1305nm/1310nm	0°C~70°C	10km	
CFP4	Part No.	Product Description	Data Rate	Wavelength	Temp.	Distance
	EOLC-851HG-S-02-MO	CFP4 SR4	4×25G 100GbE	850nm	0°C~70°C	100m
	EOLC-1HG-PCT-XX-C4	CFP4 AOC	4×25G 100GbE	850nm	0°C~70°C	100m
EOLC-161HG-S-10-L1A	CFP4 LR4	4×25G 100GbE 4×28G OTU4	1295nm/1300nm 1305nm/1310nm	0°C~70°C	10km	
CFP2	Part No.	Product Description	Data Rate	Wavelength	Temp.	Distance
	EOLC-161HG-C-10-L1A	CFP2 LR4	4×25G 100GbE 4×28G OTU4	1295nm/1300nm 1305nm/1310nm	0°C~70°C	10km
	EOLC-161HG-C-40-L1A	CFP2 ER4	4×25G 100GbE 4×28G OTU4	1295nm/1300nm 1305nm/1310nm	0°C~70°C	40km
EOLC-1HG-PCT-EH	CFP2-QSFP28 Converter	4×25G 100GbE 4×28G OTU4	N/A	0°C~70°C	N/A	
CFP	Part No.	Product Description	Data Rate	Wavelength	Temp.	Distance
	EOLC-851HG-02-MOY	CFP SR10	10×10G 100GbE 10×11.2G OTU4	850nm	0°C~70°C	100m
	EOLC-161HG-10-L1A	CFP LR4	4×25G 100GbE 4×28G OTU4	1295nm/1300nm 1305nm/1310nm	0°C~70°C	10km
EOLC-161HG-40-L1A	CFP ER4	4×25G 100GbE 4×28G OTU4	1295nm/1300nm 1305nm/1310nm	0°C~70°C	40km	
SFP28	Part No.	Product Description	Data Rate	Wavelength	Temp.	Distance
	EOLP-8528G-02-R	SFP28 SR	25G/28G (25GbE/32FC)	850nm	0°C~70°C	100m
	EOLP-25G-PCT-XX	SFP28 AOC	25G/28G (25GbE/32FC)	850nm	0°C~70°C	Up to 100m
	EOLP-1328G-10-R	SFP28 LR	25G/28G (25GbE/32FC)	1310nm	0°C~70°C	10km
EOLP-1625G-14XR	SFP28 CWDM	25G (25GbE)	1271nm/1291nm 1311nm/1331nm	0°C~70°C	10km	

<b>16G SFP+</b>	Part No.	Data Rate	Wavelength	Source	Temp.	Distance/Link Budget
	EOLP-8514G-02	14.025G	850nm	VCSEL	0°C~70°C	100m (OM3)
	EOLP-1314G-10	14.025G	1310nm	DFB	0°C~70°C	10km
	EOLP-1614G-14X	14.025G	CWDM	EML	0°C~70°C	14dB
	EOLP-1614G-14XX	14.025G	DWDM	EML	0°C~70°C	14dB
<b>SFP+, BiDi SFP+</b>	Part No.	Data Rate	Wavelength	Source	Temp.	Distance/Link Budget
	EOLP-8596-02	8G/10G	850nm	VCSEL	0°C~70°C/-40°C~85°C	300m
	EOLP-1596-A-N	10G	1550nm	EML	0°C~70°C	Up to 100km
	EOLP-BI1696-23LOL	8G/10G	1490nm/1550nm	EML	0°C~70°C	80km
	EOLP-BI1696-23LOL	8G/10G	1550nm/1490nm	EML	0°C~70°C	80km
<b>CWDM SFP+, DWDM SFP+</b>	Part No.	Data Rate	Wavelength	Source	Temp.	Distance/Link Budget
	EOPL-1696-10X	8G/10G	CWDM	DFB	0°C~70°C	10dB
	EOPL-1696-14XN	8G/10G	1470nm~1610nm	EML	0°C~70°C	14dB
	EOPL-1696-23XN	8G/10G	1470nm~1610nm	EML	0°C~70°C	23dB
	EOPL-1696-14XXN	8G/10G	DWDM	EML	0°C~70°C	14dB
	EOPL-1696-23XXN	8G/10G	DWDM	EML	0°C~70°C	23dB
<b>Wireless SFP+, SFP28</b>	Part No.	Data Rate	Wavelength	Source	Temp.	Distance/Link Budget
	EOLP-BI1696-9ADIL	8G/10G	1270nm/1330nm	DFB	-40°C~85°C	9dB
	EOLP-BI1696-9DAIL	8G/10G	1330nm/1270nm	DFB	-40°C~85°C	9dB
	EOLP-1696-14XXIN	8G/10G	DWDM	EML	-40°C~85°C	14dB (25km)
	EOLP-1696-23XXIN	8G/10G	DWDM	EML	-40°C~85°C	23dB (25km)
	EOLP-1328G-10-RI	25G/28G (25GbE/35FC)	1310nm	Cooled DFB	-40°C~85°C	10km
	EOLP-1625G-14XRI	25G (25GbE)	1271nm/1291nm 1311nm/1331nm	Cooled DFB	-40°C~85°C	10km
<b>200G, 400G</b>	<b>SFP56, QSFP56, QSFP-DD, OSFP, CFP8...</b> <b>Be the first to qualify, contact us for the latest update and samples availability!</b>					